







Over / under pressure relief device ÜU-TT- 150/200/273/300

<p>ÜU-TT- 150 / 200 / 273 / 300 Over / under pressure relief device,insulated with stainless steel protection cover;                  range: over-pressure 1 -5 mbar,                  under-pressure 1 - 5 mbar, Over and under pressure response is separately adjustable;                  Conditionally non-freezing by contact to warm digester wall and option for biogas flow-through, unaffected by condensation or rain water                  material: stainless steel 304 and 316,                  flanges DN150, DN200, DN250, DN300                  Two control window for quick check                  over-pressure:                  Art. Nr.: 80240001.2 ÜU-TT-150 1,4 - 2,8 mbar                  Art. Nr.: 80240003.2 ÜU-TT-150 3 - 5 mbar                   Art. Nr.: 80250001.2 ÜU-TT-200 1,5 - 2,8 mbar                  Art. Nr.: 80250003.2 ÜU-TT-200 3 - 5 mbar                   Art. Nr.: 80273001.2 ÜU-TT-273 1,5 - 2,8 mbar                  Art. Nr.: 80273003.2 ÜU-TT-273 3 - 5 mbar                   Art. Nr.: 80273501.2 ÜU-TT-300 1,5 - 2,8 mbar                  Art. Nr.: 80273503.2 ÜU-TT-300 3 - 5 mbar</p>	 
<p>Blow-off pipe for over pressure with flange                  DN 150 / DN 200 / DN 250 / DN 300; 2 m;                  stainless steel 1.4301                  Art. Nr.: 80280001 DN 150 2m                  Art. Nr.: 80280011 DN 200 2m                  Art. Nr.: 80280022 DN 250 2m                  Art. Nr.: 80280032 DN 300 2m</p>	 
<p>Warning sign EX INTERNATIONAL, single, on support plates stainless steel DN 150 / DN 200 / DN 250 / DN 300 completely                  Art. Nr.: 80240009 DN 150                  Art. Nr.: 80250009 DN 200                  Art. Nr.: 80260007 DN 250                  Art. Nr.: 80270007 DN 300</p>	 

<p>Butterfly valve EBRO cast iron / stainless steel / NBR for gas                  Inter flange type / end of pipe type                  DN 100.: 70100100 / 70150100                  DN 150.: 70100150 / 70150150                  DN 200: 70100200 / 70150200                  DN 250: 70100250 / 70150250</p>	
<p>T-piece port for ÜU-TT- 150 / 200 / 273 / 300 complete with blind-cap, gas-proof-seal and screws in stainless steel.                  PE-HD10 with DIN-flange with DN 150 / DN 200 / DN 250 / DN 300.                  for spacing bush DN 150 / DN 200 / DN 250 / DN 300 or core drill hole !!                  Art. Nr.: 80240007 DN 150                  Art. Nr.: 80250007 DN 200                  Art. Nr.: 80273007 DN 250 (TT-273)                  Art. Nr.: 80273507 DN 300</p>	
<p>T-piece port for ÜU-TT- 150 / 200 Over / under pressure relief device, complete with blankcap, gas-proof-seal and screws in stainless steel.                  stainless steel 316 with DIN-flange                  Art. Nr.: 80240008 DN 150 Ø 159 mm                  Art. Nr.: 80250008 DN 200 Ø 219 mm                  Art. Nr.: 80250016 DN 250 Ø 273 mm</p>	
<p>Spacing tube DN 300 &amp; DN 400, as tubular insert in concrete walls, PVC with rubber ribs, for direct assembly of Bull's-eye, filled with sturdy foam disks for stiffening,                  available in 20, 25, 30 cm, also available in other requested widths                  Art. Nr.: 80120035 DN 300 20cm                  Art. Nr.: 80120036 DN 300 25cm                  Art. Nr.: 80120037 DN 300 30cm                  Art. Nr.: 80124035 DN 400 20cm                  Art. Nr.: 80124036 DN 400 25cm                  Art. Nr.: 80124037 DN 400 30cm</p>	
<p>Goose neck on T-piece DN 150 / DN 200 / DN 250 for TT-150 / 200 / 273, comprising PP plug-in socket moulded parts for fitting on to T-connector inside the digester in order to prevent the substrate from entering                  Complete with stainless steel 316 stainless steel clasp and stainless steel profile, incl. fasteners                  Art. Nr.: 80240010 DN150 for PE-HD and stainless steel T-piece                  Art. Nr.: 80250010 DN200 only for PE                  Art. Nr.: 80273010 DN250 only for PE</p>	

<p>Sensor for ÜU-TT 150 / 200 / 273 / 300 Over / under pressure relief device indicating opening at overpressure, with stainless steel double-flange, DN 150 / DN 200 / DN 250 / DN 300 ATEX-sensor with 2m connection cable and cable lead-through</p> <p>Art. Nr.: 80240011 DN 150              Art. Nr.: 80250011 DN 200              Art. Nr.: 80273011 DN 273              Art. Nr.: 80273511 DN 300</p>	
<p>Heating system for ÜU-TT- 150 / 200 / 273 / 300 Over / under pressure relief device, ATEX-approved for ex-zone, 230 Volt, with thermostat 20°C and safety limiter, tested and approved DIN-VDE 0100, stainless steel 316 with explosion-proof permission zone 1+2, temperature classification T1</p> <p>Art. Nr.: 75500009 E</p>	
<p>ÜU-TT - 150 / 200 operating lever for mechanical opening with damper, made of stainless steel incl. 5 m/ 3mm stainless steel wire rope and reverse roller</p> <p>Art. Nr.: 80240015 ÜU-TT-150              Art. Nr.: 80250015 ÜU-TT-200</p>	